



eXpert IPC solutions

www.elt-ipc.com / (909) 598-1824 / sales@elt-ipc.com

PLP-A758



Systems

Processor	Intel Atom Cedar View N2600 1.6 GHz Dual Core
System Chipset	Intel NM10
System Memory	Onboard DDR3 2GB 800 MHz
Power Consumption	Max. 15.2W @ 12V

I/O Ports

USB	2 x USB 2.0 Type A. USB 4/5
Serial Port	1 x RS-232/422/485 DB-9, Default RS-232 1 x RS-232 DB-9, COM2
Audio	1 x Line Out 3.5mm Jack
LAN	2 x GbE RJ-45 LAN Port
Power	3 Pins Terminal Block Connector, DC Power Input

Touch Screen

Type	Resistive Touch
Interface	RS-232
Light Transmission (%)	80

Environment

Operation Temperature	0° ~ 50°C
Storage Temperature	-20°C ~ 60°C
Humidity	10% ~ 90%
Certificate	CE / FCC Class A

Storage

HDD	1 x 1.8" SATA 2 (Half Size)
Movable Device	1 x Internal SD Slot

Expansion

Expansion Bus	1 x Mini-PCle Half Size
---------------	-------------------------

Display

LCD	8" TFT-LCD
Touch Screen	Resistive
Max. Resolution	800x600
Max. Color	16.2M
View Angle	H: 140° / V: 125°

Power

Power Input	9 ~ 36V DC
-------------	------------

Mechanical

Construction	Silver Aluminum Front Bezel And Chassis
IP Rating	IP65 Front Panel
Mounting	Panel Mounting, VESA 75x75
Dimension (WxHxD)	231x176x51mm
Net Weight (kg)	1.8