

PLP-P26128



Specifications

| | |
|-------------------|--|
| Processor | Intel Atom Cedar View N2600 1.86GHz Dual Core |
| System Chipset | Intel NM10 |
| System Memory | Onboard DDR3 2GB 800MHz |
| Power Consumption | Max. 15.2 W @ 12V |
| I/O Ports | |
| USB | 2 x USB 2.0 Type A USB 4/5 |
| Serial Port | 1 x RS-232/422/485 DB-9, COM1, Default RS-232 1 x RS-232 DB-9, COM2 |
| Audio | 1 x Line Out 3.5MM Jack |
| LAN | 2 x GbE RJ-45 LAN Port |
| Power | 3 Pins Terminal Block Connector DC Power Input |

Storage

| | |
|---------|----------------------|
| HDD | 1 x 1.8" SATA 2 |
| Movable | 1 x Internal SD Slot |

Environment

| | |
|-----------------|---------------------------------|
| Operation Temp. | 0° ~ 50°C |
| Storage Temp. | -20° ~ 60°C |
| Humidity | 10 ~ 90% @ 40°C, Non-Condensing |
| Certificate | CE / FCC Class A |

Power

| | |
|-------------|------------|
| Power Input | 9 ~ 36V DC |
|-------------|------------|

Display

| | |
|-----------------|-------------------|
| LCD | 8" TFT-LCD |
| Touch Screen | Resistive |
| Max. Resolution | 800 x 600 |
| Max. Color | 16.2M |
| View Angle | H: 140° / V: 125° |
| Brightness | 350cd/m2 |

Touch Screen

| | |
|------------------------|-----------------|
| Type | Resistive Touch |
| Interface | RS-232 |
| Light Transmission (%) | 80 |

Mechanical

| | |
|-------------------|---|
| Construction | Silver Aluminum Front Bezel and Chassis |
| IP Rating | IP65 Front Panel |
| Mounting | Panel Mounting, VESA 75 x 75 |
| Dimension (WxHxD) | 231 x 176 x 51mm |
| Net Weight (Kgs) | 1.8 |

Expansion

| | |
|---------------|-------------------------|
| Expansion Bus | 1 x Mini-PCIe Half Size |
|---------------|-------------------------|