

PLP-P26138



Specifications

Processor	Intel Atom D2550
System Chipset	Intel NM10
System Memory	1x DDR3 SO-DIMM Socket Up TO 4GB
Power Consumption	DC In 9~36V
I/O Ports	
USB	2x USB 2.0
Serial Port	2x COM Port (Support +5V/12V/RI Selectable) COM2 For RS232/422/485 Selectable
Audio	1x Line Out, 1x MIC In
LAN	2x LAN (10/100/1000 Mbps)
Power	DC In 9~36V
Storage	
HDD	1 x 2.5" SATA HDD
Movable	N/A
Environment	
Operation Temp.	0° ~ 50°C
Storage Temp.	-20° ~ 60°C
Humidity	10 ~ 90% @ 40°C, Non-Condensing
Certificate	CE / FCC
Power	
Power Input	9 ~ 36V DC

Display

LCD	8.4" LED Backlight
Touch Screen	Resistive
Max. Resolution	800 x 600
Max. Color	N/A
View Angle	N/A
Brightness	N/A

Touch Screen

Type	Resistive Touch
Interface	USB
Light Transmission (%)	N/A

Mechanical

Construction	Aluminum Front Bezel
IP Rating	IP65 Front Panel
Mounting	VESA 75
Dimension (WxHxD)	252 x 184.6 x 71mm
Net Weight (Kgs)	2.69

Expansion

Expansion Bus	1x CFast Slot, 1x MINI PCIe Slot, 1x SIM Card Slot
---------------	---